

DESCALING LIQUID

Wilhelmsen Ships Service AS

Catalogue number: 571653 (25 liter) Version No: 3.3

Safety Data Sheet (Conforms to Regulation (EU) No 2015/830)

Issue Date: 04/10/2016 Print Date: 28/12/2018 L.REACH.NOR.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product Identifier

Product name	DESCALING LIQUID		
Synonyms	t Available		
Proper shipping name	/DROCHLORIC ACID		
Other means of identification	571653 (25 liter), 571653		

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Category Chemical	PC35 Washing and cleaning products (including solventbased products)				
Sectors of Use	SU3 Industrial uses: Uses of substances as such or in preparations* at industrial sites				
Relevant identified uses	atmosphere developing. Before starting consider control of exposure by mechanical ventilation.				
Uses advised against					

1.3. Details of the supplier of the safety data sheet

Registered company name	Wilhelmsen Ships Service AS	Outback (M)SDS portal: http://jr.chemwatch.net/outb/account /autologin?login=wilhelmsen	Wilhelmsen Ships Service AS*
Address Strandveien 20 Lysaker 1366 Norway		Use our Outback portal to obtain our (M)SDSs in other languages and/or format For questions relating to our SDSs please use Email: WSS.GLOBAL.SDSINFO@wilhelmsen.com Norway	Willem Barentszstraat 50 Rotterdam Netherlands
Telephone +47 67 58 40 00 Fax Not Available Website http://www.wilhelmsen.com/		Not Available	+31 10 4877 777
		Not Available	+31 10 4877888
		Not Available	http://www.wilhelmsen.com
Email wss.norway.cs@wilhelmsen.com		Not Available	wss.rotterdam@wilhelmsen.com

1.4. Emergency telephone number

	Association / Organisation	Giftinformasjonssentralen - 24 timer	American Chemistry Council 24hrs - Chemtrec	Dutch nat. poison centre
	Emergency telephone numbers	+47 22591300	+1 703 527 3887	+ 31 30 274 88 88
	Other emergency telephone numbers Not Available		(800) 424 9300	Not Available

2.1. Classification of the substance or mixture

Classification according
to regulation (EC) No
1272/2008 [CLP] ^[1]

H290 - Metal Corrosion Category 1, H314 - Skin Corrosion/Irritation Category 1A, H335 - Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)





SIGNAL WORD

DANGER

Hazard statement(s)

H290	May be corrosive to metals.	
H314	Causes severe skin burns and eye damage.	
H335	H335 May cause respiratory irritation.	

Supplementary statement(s)

Not Applicable

Precautionary statement(s) General

P101 If medical advice is needed, have product container or label at hand.	
P102 Keep out of reach of children.	
P103 Read label before use.	

Precautionary statement(s) Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.		
P271 Use only outdoors or in a well-ventilated area.			
P280 Wear protective gloves/protective clothing/eye protection/face protection.			
P234 Keep only in original packaging.			

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P310	Immediately call a POISON CENTER/doctor/physician/first aider.		
P363	Wash contaminated clothing before reuse.		
P390	Absorb spillage to prevent material damage.		
P304+P340	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.		

Precautionary statement(s) Storage

P405 Store locked up.		Store locked up.
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

REACh - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP]
1.7647-01-0. 2.231-595-7 3.017-002-00-2 017-002-01-X 4.01-2119484862-27- XXXX 01-2120762784-43- XXXX 01-2120066883-46-XXXX	33-35	hydrogen Acute Toxicity (Inhalation) Category 3, Serious Eye Damage Category 1, Skin Corrosion/Irritation Category 1A; H331, H314, EUH044 [1]	
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L * EU IOELVs available		

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first air procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- $\bullet \ \ \text{Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise. } \\$
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- ▶ DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- ▶ Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- ▶ Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN

• Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.

▶ Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes.

 DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- ▶ Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
5.3. Advice for firefighte	ers
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acrid smoke. Decomposition may produce toxic fumes of: hydrogen chloride Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

			• .						
Minor Spills	 Drains for storage or disposal of ma Check regularly feed to Clean up all spills Avoid breathing to Control personal Contain and absorb Wipe up. Place in a suitable 	terial. for spills and I for spills and I for spills and I for spill with s	leaks. contact with skin ar the substance, by t and, earth, inert m	nd ey using ateria	es. protectal or vei	ive eq	uipment.	d dilution of spills before disch	narge
	Chemical Class:acidi For release onto lan SORBENT TYPE LAND SPILL - SMAL	d: recommend	. •	in or	der of p		LECTION	LIMITATIONS	
Major Spills	foamed glass - pillo expanded mineral - foamed glass - part	particulate		1 2 2	throw show	el	pitchfork shovel shovel	R, P, DGC, RT R, I, W, P, DGC R, W, P, DGC	
	LAND SPILL - MED	IUM							

expanded mineral -particulate	1	blower	skiploader	R, I, W, P, DGC
foamed glass- particulate	2	blower	skiploader	R, W, P, DGC
foamed glass - particulate	3	throw	skiploader	R, W, P, DGC

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT:Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988

- ▶ Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- ▶ Stop leak if safe to do so.
- ▶ Contain spill with sand, earth or vermiculite.
- ► Collect recoverable product into labelled containers for recycling.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling	Contains low boiling substance: Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately. Check for bulging containers. Vent periodically Always release caps or seals slowly to ensure slow dissipation of vapours Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke.
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Lined metal can, lined metal pail/ can.
Plastic pail.
Polyliner drum.
Packing as recommended by manufacturer.
Check all containers are clearly labelled and free from leaks.
For low viscosity materials

► Check regularly for spills and leaks

► DO NOT use aluminium or galvanised containers

- Suitable container
- ▶ Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
- ► Cans with friction closures and
- ▶ low pressure tubes and cartridges

may be used.

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

Storage incompatibility

- Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0
- Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts neutralisation

- can generate dangerously large amounts of heat in small spaces.
- The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.
- Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.
- ▶ Contact with moisture or water may generate heat causing ignition
- ► Reacts vigorously with alkalis
- Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.



X - Must not be stored together

May be stored together with specific preventions

— May be stored together

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	hydrogen chloride	Hydrogen Chloride	5 ppm / 8 mg/m3	15 mg/m3 / 10 ppm	Not Available	Not Available
Norway regulations on action values and limit values for physical and chemical factors in the work environment and infection risk groups for biological factors (Norwegian)	hydrogen chloride	Hydrogenklorid	Not Available	Not Available	5 ppm / 7 mg/m3	TE

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
hydrogen chloride	Hydrogen chloride; (Hydrochloric acid)	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
hydrogen chloride	50 ppm	Not Available

MATERIAL DATA

for hydrogen chloride:

Odour Threshold Value: 0.262 ppm (detection), 10.06 ppm (recognition)

NOTE: Detector tubes for hydrochloric acid, measuring in excess of 1 ppm, are available commercially.

Hydrogen chloride is a strong irritant to the eyes, mucous membranes and skin. Chronic exposure produces a corrosive action on the teeth. Reports of respiratory irritation following short-term exposure at 5 ppm have lead to the recommended TLV-C. There is no indication that skin contact with hydrogen chloride elicits systemic poisoning and a skin designation has not been applied.

Exposure of humans to hydrogen chloride at 50 to 100 ppm for 1 hour is reported to be barely tolerable; 35 ppm caused irritation of the throat on short exposure and 10 ppm was the maximal concentration for prolonged exposure. It has been stated that hydrogen chloride at concentrations of 5 ppm is immediately irritating.

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

Classification into classes follows:

ClassOSF Description

- A 550 Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities
- B 26-550As "A" for 50-90% of persons being distracted
 - 1-26 As "A" for less than 50% of persons being distracted
- D 0.18-1 10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
- E <0.18 As "D" for less than 10% of persons aware of being tested

8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

8.2.1. Appropriate engineering controls

Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

8.2.2. Personal protection











- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
- Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.

Eye and face protection

- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- ▶ Alternatively a gas mask may replace splash goggles and face shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Skin protection

See Hand protection below

Hands/feet protection

- ▶ Elbow length PVC gloves
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

Body protection

See Other protection below

Other protection

- Overalls.
- PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- ▶ Eyewash unit
 - Ensure there is ready access to a safety shower.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid, pale yellow, soluble in water		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	1	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	~100-760	Molecular weight (g/mol)	Not Available

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	105.5	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	1.26	VOC g/L	Not Available

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2. Chemical stability	► Contact with alkaline material liberates heat
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects; these may be fatal.

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Inhaled

Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema.

Hydrogen chloride (HCI) vapour or fumes present a hazard from a single acute exposure. Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes.

Inhalation of HCI may cause choking, coughing, burning sensation and may cause ulceration of the nose, throat and larynx. Fluid on the lungs followed by generalised lung damage may follow.

Breathing of HCI vapour may aggravate asthma and inflammatory or fibrotic pulmonary disease.

High concentrations cause necrosis of the tracheal and bronchial epithelium, pulmonary oedema, atelectasis and emphysema and damage to the pulmonary blood vessels and liver.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

Ingestion

Ingestion of acidic corrosives may produce circumoral burns with a distinct discolouration of the mucous membranes of the mouth, throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Oedema of the epiglottis may produce respiratory distress and possibly, asphyxia. Nausea, vomiting, diarrhoea and a pronounced thirst may occur. More severe exposures may produce a vomitus containing fresh or dark blood and large shreds of mucosa. Shock, with marked hypotension, weak and rapid pulse, shallow respiration and clammy skin may be symptomatic of the exposure. Circulatory collapse may, if left untreated, result in renal failure.

The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.

Skin Contact

Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is

	suitably protected. When applied to the eye(s) of animals, the material properties after instillation.	roduces severe ocular lesions which are present twenty-four hours o	
Eye	Direct eye contact with acid corrosives may produce pain, lachrymation, photophobia and burns. Mild burns of the epithelia generally recover rapidly and completely. Severe burns produce long-lasting and possible irreversible damage. The appearance of the burn may not be apparent for several weeks after the initial contact. The cornea may ultimately become deeply vascularised and opaque resulting in blindness.		
Chronic	mouth and necrosis (rarely) of the jaw. Bronchial irrita ensue. Gastrointestinal disturbances may also occur. The impact of inhaled acidic agents on the respiratory physicochemical characteristics, e.g., gas versus aerulung); water solubility (more soluble agents are more of information on the particle size of aerosols involve principal deposition site within the respiratory tract. Long-term exposure to respiratory irritants may result systemic problems. Limited evidence suggests that repeated or long-term involving organs or biochemical systems. Chronic minor exposure to hydrogen chloride (HCI) valueding of the nose and gums; and ulceration of the Repeated exposures of animals to concentrations of	about 34 ppm HCl produced no immediate toxic effects. gastritis and a number of cases of chronic bronchitis have also bee	
	TOXICITY	IRRITATION	
DESCALING LIQUID	Not Available	Not Available	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: >5010 mg/kg ^[2]	Eye (rabbit): 5 mg/30s - mild	
hydronon oblorido	Inhalation (rat) LC50: 780.108879 mg/l/1h[2]		
hydrogen chloride	Illinaiation (rat) EC30. 760.106079 mg/// m	I .	
hydrogen chloride	Oral (rat) LD50: =700 mg/kg ^[2]		
hydrogen chloride Legend:	Oral (rat) LD50: =700 mg/kg ^[2]	stances - Acute toxicity 2.* Value obtained from manufacturer's SDS.	

DESCALING LIQUID

pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airways from direct exposure to inhaled acidic mists, just as mucous plays an important role in protecting the gastric epithelium from its auto-secreted hydrochloric acid. In considering whether pH itself induces genotoxic events in vivo in the respiratory system, comparison should be made with the human stomach, in which gastric juice may be at pH 1-2 under fasting or nocturnal conditions, and with the human urinary bladder, in which the pH of urine can range from <5 to=""> 7 and normally averages 6.2. Furthermore, exposures to low pH in vivo differ from exposures *in vitro* in that, *in vivo*, only a portion of the cell surface is subjected to the adverse conditions, so that perturbation of intracellular homeostasis may be maintained more readily than in vitro.

HYDROGEN CHLORIDE

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

4701 ppm/30m

DESCALING LIQUID & HYDROGEN CHLORIDE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

Acute Toxicity	×	Carcinogenicity	X
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	•
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

DESCALING LIQUID	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	70.057mg/L	3
hydrogen chloride	EC50	96	Algae or other aquatic plants	344.947mg/L	3
	NOEC	0.08	Fish	10mg/L	4
Legend:	Toxicity 3. EP Data 5. ECET	IWIN Suite V3.12 (QSAR) - Aqua	pe ECHA Registered Substances - Ecotoxico tic Toxicity Data (Estimated) 4. US EPA, Eco Data 6. NITE (Japan) - Bioconcentration Data	otox database - Aqua	

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

Although inorganic chloride ions are not normally considered toxic they can exist in effluents at acutely toxic levels (chloride >3000 mg/l). The resulting salinity can exceed the tolerances of most freshwater organisms.

Inorganic chlorine eventually finds its way into the aqueous compartment and as such is bioavailable. Incidental exposure to inorganic chloride may occur in occupational settings where chemicals management policies are improperly applied. The toxicity of chloride salts depends on the counter-ion (cation) present; that of chloride itself is unknown. Chloride toxicity has not been observed in humans except in the special case of impaired sodium chloride metabolism, e.g. in congestive heart failure. Healthy individuals can tolerate the intake of large quantities of chloride provided that there is a concomitant intake of fresh water.

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
hydrogen chloride	LOW	LOW

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
hydrogen chloride	LOW (LogKOW = 0.5392)

12.4. Mobility in soil

Ingredient	Mobility
hydrogen chloride	LOW (KOC = 14.3)

12.5.Results of PBT and vPvB assessment

	Р	В	Т
Relevant available data	Not Applicable	Not Applicable	Not Applicable
PBT Criteria fulfilled?	Not Applicable	Not Applicable	Not Applicable

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

- ► Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Product / Packaging disposal

- ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

▶ Recycle wherever possible.
 ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 ▶ Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
 ▶ Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.
 Waste treatment options
 Not Available
 Sewage disposal options

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

NO

Not Applicable

Land transport (ADR)

14.1. UN number	1789		
14.2. UN proper shipping name	HYDROCHLORIC ACID		
14.3. Transport hazard class(es)	Class 8 Subrisk Not Applicable		
14.4. Packing group	II .		
14.5. Environmental hazard	Not Applicable		
	Hazard identification (Kemler)	80	
	Classification code	C1	
14.6. Special precautions for user	Hazard Label	8	
TOT USET	Special provisions	520	
	Limited quantity	1L	

Air transport (ICAO-IATA / DGR)

14.1. UN number	1789			
14.2. UN proper shipping name	Hydrochloric acid			
	ICAO/IATA Class 8			
14.3. Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable		
Class(es)	ERG Code	8L		
14.4. Packing group	П			
14.5. Environmental hazard	Not Applicable			
	Special provisions		A3 A803	
	Cargo Only Packing Instructions		855	
	Cargo Only Maximum Qty / Pack		30 L	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		851	
	Passenger and Cargo Maximum Qty / Pack		1 L	
	Passenger and Cargo	Limited Quantity Packing Instructions	Y840	
	Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Limited Maximum Qty / Pack		0.5 L	

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1789
-----------------	------

14.2. UN proper shipping name	HYDROCHLORIC ACID		
14.3. Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable		
14.4. Packing group	II		
14.5. Environmental hazard	Not Applicable		
	EMS Number F-A , S-B		
14.6. Special precautions	Special provisions Not Applicable		
for user	Limited Quantities 1 L		

Inland waterways transport (ADN)

14.1. UN number	1789			
14.2. UN proper shipping name	HYDROCHLORIC ACID			
14.3. Transport hazard class(es)	8 Not Applicable			
14.4. Packing group	II			
14.5. Environmental hazard	Not Applicable			
	Classification code	C1		
	Special provisions	520		
14.6. Special precautions for user	Limited quantity	1 L		
	Equipment required I	PP, EP		
	Fire cones number	0		

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

HYDROGEN CHLORIDE(7647-01-0.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances - updated by ATP: 31

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Air Transport Association (IATA) Dangerous Goods Regulations
- Prohibited List Passenger and Cargo Aircraft

Norway regulations on action values and limit values for physical and chemical factors in the work environment and infection risk groups for biological factors (Norwegian)

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2015/830; Regulation (EC) No 1272/2008 as updated through ATPs.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
hydrogen chloride	7647-01-0.	017-002-00-2l017-002-01-X	01-2119484862-27-XXXXI01-2120762784-43-XXXXI01-2120066883-46-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Corr. 1A; Acute Tox. 3	GHS05; GHS04; GHS06; Dgr	H314; H331
1	Skin Corr. 1A; Acute Tox. 3	GHS05; GHS04; GHS06; Dgr	H314; H331
1	Skin Corr. 1B; STOT SE 3	GHS05; Dgr	H314; H335
1	Met. Corr. 1; Skin Corr. 1B; STOT SE 3	GHS05; Dgr	H290; H314; H335

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory Status

National Inventory	Status	
Australia - AICS	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (hydrogen chloride)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Legend:	Yes = All ingredients are on the inventory No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Revision Date	04/10/2016
Initial Date	27/09/2016

CONTACT POINT

- For quotations contact your local Customer Services - http://wssdirectory.wilhelmsen.com/#/customerservices - - Responsible for safety data sheet Wilhelmsen Ships Service AS - Prepared by: Product HSE Manager, - Email: WSS.GLOBAL.SDSINFO@wilhelmsen.com - Telephone: Tel.: +31 10 4877775

Full text Risk and Hazard codes

H331	Toxic if inhaled.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit_\circ

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Notes

"This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships."

